



# PASSENGER CAR & LIGHT TRUCK Tires

**BROCHURE**



# PRODUCTS



**HH601**

**HU801**



**HHT01**

**HRT01**



**T01**

**W01**



# HH601



ECONOMY



QUIET



COMFORT



WET GRIP



HP MAXIMUM

## Lower heat generation, more efficient

Optimized section design to reduce tire heat generation, more environmentally friendly.

## Wear resistance, longer service life

Optimized anti-wear compound and pattern design to improve the stability and tire wear resistance for longer service life.

## Low noise, excellent handling experience

Five pitches design can effectively dissipate peak noise energy; a closed shoulder design reduces noise while ensuring wet grip performance, providing the driver with a comfortable ride.



| Rim | Size      | LI/SS | Load Range | Section Width | Overall Diameter | Std. Rim | Standard Pressure (Kpa) |
|-----|-----------|-------|------------|---------------|------------------|----------|-------------------------|
| 13  | 175/70R13 | 82H   | SL         | 177           | 576              | 5.00B    | 300                     |
|     | 185/70R13 | 86T   | SL         | 189           | 590              | 5.50B    | 300                     |
|     | 175/65R14 | 82H   | SL         | 177           | 584              | 5J       | 300                     |
|     | 175/70R14 | 84H   | SL         | 177           | 602              | 5J       | 300                     |
| 14  | 185/60R14 | 82H   | SL         | 189           | 578              | 5 1/2J   | 300                     |
|     | 185/65R14 | 86H   | SL         | 189           | 596              | 5 1/2J   | 300                     |
|     | 195/70R14 | 91H   | SL         | 201           | 630              | 6J       | 300                     |
|     | 175/65R15 | 84H   | SL         | 177           | 609              | 5J       | 300                     |
| 15  | 185/55R15 | 82V   | SL         | 194           | 585              | 6J       | 300                     |
|     | 185/60R15 | 88H   | XL         | 189           | 603              | 5 1/2J   | 340                     |
|     | 185/65R15 | 88H   | SL         | 189           | 621              | 5 1/2J   | 300                     |
|     | 195/60R15 | 88H   | SL         | 201           | 615              | 6J       | 300                     |
|     | 195/65R15 | 91V   | SL         | 201           | 635              | 6J       | 300                     |
|     | 205/60R15 | 91V   | SL         | 209           | 627              | 6J       | 300                     |
|     | 205/65R15 | 94V   | SL         | 209           | 647              | 6J       | 300                     |
|     | 205/70R15 | 96H   | SL         | 209           | 669              | 6J       | 300                     |
| 16  | 195/50R16 | 88V   | XL         | 201           | 602              | 6J       | 340                     |
|     | 195/55R16 | 91V   | XL         | 201           | 620              | 6J       | 340                     |
|     | 205/50R16 | 91V   | XL         | 214           | 612              | 6 1/2J   | 340                     |
|     | 205/55R16 | 91V   | XL         | 214           | 632              | 6 1/2J   | 340                     |
|     | 205/60R16 | 92V   | SL         | 209           | 652              | 6J       | 300                     |
|     | 205/65R16 | 99H   | XL         | 209           | 672              | 6J       | 340                     |
|     | 215/55R16 | 97V   | XL         | 226           | 642              | 7J       | 340                     |
|     | 215/60R16 | 99V   | XL         | 221           | 664              | 6 1/2J   | 340                     |
|     | 215/65R16 | 98H   | SL         | 221           | 686              | 6 1/2J   | 300                     |
|     | 225/60R16 | 98H   | SL         | 228           | 676              | 6 1/2J   | 300                     |
|     | 225/65R16 | 100H  | SL         | 228           | 698              | 6 1/2J   | 300                     |
|     | 235/65R16 | 107H  | XL         | 240           | 712              | 7J       | 340                     |

# HU801



HANDLING



WET GRIP



QUIET



COMFORT



**UHP OPTIMUM**



## Excellent handling performance

Widen tire shoulder design provides better grip when fast cornering;  
Strengthened center rib to further enhance the handling performance of the tire.

## All season better grip performance

Asymmetric pattern design: inside denser pieces of steel sheet and outside large and strong tread blocks for better grip on wet and dry road.

## Low noise, better riding experience

Five pitches design can effectively dissipate peak noise energy, enjoy a quiet journey.

| Rim | Size       | LI/SS | Load Range | Section Width | Overall Diameter | Std. Rim | Standard Pressure (Kpa) |
|-----|------------|-------|------------|---------------|------------------|----------|-------------------------|
| 16  | 205/50ZR16 | 91W   | XL         | 214           | 612              | 6 1/2J   | 340                     |
|     | 225/55ZR16 | 99W   | XL         | 233           | 654              | 7J       | 340                     |
|     | 205/45ZR17 | 88W   | XL         | 206           | 616              | 7J       | 340                     |
|     | 205/50ZR17 | 93W   | XL         | 214           | 638              | 6 1/2J   | 340                     |
|     | 205/55ZR17 | 91W   | SL         | 214           | 658              | 6 1/2J   | 300                     |
|     | 215/45ZR17 | 91W   | XL         | 213           | 626              | 7J       | 340                     |
|     | 215/50ZR17 | 95W   | XL         | 226           | 648              | 7J       | 340                     |
| 17  | 215/55ZR17 | 98W   | XL         | 226           | 668              | 7J       | 340                     |
|     | 225/45ZR17 | 94W   | XL         | 225           | 634              | 7 1/2J   | 340                     |
|     | 225/50ZR17 | 98W   | XL         | 233           | 658              | 7J       | 340                     |
|     | 225/55ZR17 | 101W  | XL         | 233           | 680              | 7J       | 340                     |
|     | 235/45ZR17 | 97W   | XL         | 236           | 644              | 8J       | 340                     |
|     | 235/50ZR17 | 100W  | XL         | 245           | 668              | 7 1/2J   | 340                     |
|     | 235/55ZR17 | 103W  | XL         | 245           | 690              | 7 1/2J   | 340                     |
|     | 245/40ZR17 | 95W   | XL         | 248           | 628              | 8 1/2J   | 340                     |
|     | 245/45ZR17 | 99W   | XL         | 243           | 652              | 8J       | 340                     |
|     | 215/40ZR18 | 89W   | XL         | 218           | 629              | 7 1/2J   | 340                     |
| 18  | 215/45ZR18 | 93W   | XL         | 213           | 651              | 7J       | 340                     |
|     | 215/55ZR18 | 99W   | XL         | 226           | 693              | 7J       | 340                     |
|     | 225/40ZR18 | 92W   | XL         | 230           | 637              | 8J       | 340                     |
|     | 225/45ZR18 | 95W   | XL         | 225           | 659              | 7 1/2J   | 340                     |
|     | 225/50R18  | 99W   | XL         | 233           | 683              | 7J       | 340                     |
|     | 225/55R18  | 102W  | XL         | 233           | 705              | 7J       | 340                     |
|     | 235/40ZR18 | 95W   | XL         | 241           | 645              | 8 1/2J   | 340                     |
|     | 235/45ZR18 | 98W   | XL         | 236           | 669              | 8J       | 340                     |
|     | 235/50ZR18 | 101W  | XL         | 245           | 693              | 7 1/2J   | 340                     |
|     | 235/55R18  | 104W  | XL         | 245           | 715              | 7 1/2J   | 340                     |
|     | 245/40ZR18 | 97W   | XL         | 248           | 653              | 8 1/2J   | 340                     |
|     | 245/45ZR18 | 100W  | XL         | 243           | 677              | 8J       | 340                     |
|     | 245/55R18  | 103W  | SL         | 253           | 727              | 7 1/2J   | 300                     |
| 19  | 245/50ZR18 | 104W  | XL         | 253           | 703              | 7 1/2J   | 340                     |
|     | 255/35ZR18 | 94W   | XL         | 260           | 635              | 9J       | 340                     |
|     | 225/40ZR19 | 93Y   | XL         | 230           | 663              | 8J       | 340                     |
|     | 225/45ZR19 | 96W   | XL         | 225           | 685              | 7 1/2J   | 340                     |
|     | 225/55ZR19 | 99W   | SL         | 233           | 731              | 7J       | 300                     |
|     | 235/40ZR19 | 96Y   | XL         | 241           | 671              | 8 1/2J   | 340                     |
|     | 235/45R19  | 95W   | SL         | 236           | 695              | 8J       | 340                     |
|     | 235/50ZR19 | 103W  | XL         | 245           | 719              | 7 1/2J   | 340                     |
|     | 235/50R19  | 103W  | XL         | 245           | 719              | 7 1/2J   | 340                     |
|     | 235/55R19  | 105W  | XL         | 245           | 741              | 7 1/2J   | 340                     |
|     | 245/40R19  | 98W   | XL         | 248           | 679              | 8 1/2J   | 340                     |
|     | 245/45R19  | 102W  | XL         | 243           | 703              | 8J       | 340                     |
|     | 245/55R19  | 103W  | SL         | 253           | 753              | 7 1/2J   | 300                     |
|     | 255/35ZR19 | 96W   | XL         | 260           | 661              | 9J       | 340                     |
|     | 255/40ZR19 | 100W  | XL         | 260           | 687              | 9J       | 340                     |
| 20  | 255/50R19  | 107W  | XL         | 265           | 739              | 8J       | 340                     |
|     | 235/55ZR20 | 105W  | XL         | 245           | 766              | 7 1/2J   | 340                     |
|     | 245/35ZR20 | 95Y   | XL         | 248           | 680              | 8 1/2J   | 340                     |
|     | 245/40ZR20 | 99Y   | XL         | 248           | 704              | 8 1/2J   | 340                     |
|     | 245/45ZR20 | 103W  | XL         | 243           | 728              | 8J       | 340                     |
|     | 245/50R20  | 102W  | SL         | 253           | 754              | 7 1/2J   | 300                     |
|     | 255/45ZR20 | 105W  | XL         | 255           | 738              | 8 1/2J   | 340                     |
|     | 255/50R20  | 109W  | XL         | 265           | 764              | 8J       | 340                     |
|     | 255/55R20  | 110W  | XL         | 265           | 788              | 8J       | 340                     |
|     | 265/50ZR20 | 111W  | XL         | 277           | 774              | 8 1/2J   | 340                     |
| 22  | 275/40ZR20 | 106Y  | XL         | 278           | 728              | 9 1/2J   | 340                     |
|     | 275/45ZR20 | 110W  | SL         | 273           | 756              | 9J       | 300                     |
|     | 275/55ZR20 | 117W  | XL         | 284           | 810              | 8 1/2J   | 340                     |
|     | 265/35ZR22 | 102Y  | XL         | 271           | 745              | 9 1/2J   | 340                     |
|     | 275/50ZR22 | 111W  | SL         | 284           | 835              | 8 1/2J   | 300                     |
| 26  | 285/45R22  | 114W  | XL         | 285           | 81               | 5        | 9 1/2J                  |
|     | 305/30ZR26 | 109W  | XL         | 313           | 844              | 11J      | 340                     |

# HHTO1



HANDLING



ANTI-WEAR



SAFE



WET GRIP



**SUV LANDRIDER**

## Excellent handling performance, better grip

The robust lower sidewall and bead design improves tire response and makes handling easy; Multi-angle grooves are designed to provide ample grip for the vehicle when accelerating and braking on straightaways and curves.

## Wear resistance, safe journey

Optimized placement of the tread blocks and grooves provides excellent ride comfort and wear resistance; All-season all-terrain tread rubber invention patent formula : rare earth catalytic polymer and high structural carbon black design, dramatically improve the tread rubber wear resistance.

## Passionate off-road driving experience

FEA-optimized tread block layout balances grounding stress distribution and improves street driving stability; Wide blocks with better off-road performance are used on the shoulders, enjoying the comfortable and safe driving in off-road conditions.



| Rim | Size        | LI/SS    | Load Range | Section Width | Overall Diameter | Std. Rim | Standard Pressure (Kpa) |
|-----|-------------|----------|------------|---------------|------------------|----------|-------------------------|
| 15  | P225/70R15  | 100H     | SL         | 228           | 697              | 6 1/2J   | 300                     |
|     | P235/75R15  | 105H     | SL         | 235           | 733              | 6 1/2J   | 300                     |
|     | LT235/75R15 | 110/107Q | 8PR        | 235           | 733              | 6 1/2J   | 450                     |
|     | LT215/85R16 | 115/112Q | 10PR       | 216           | 772              | 6J       | 550                     |
|     | P225/70R16  | 103H     | SL         | 228           | 722              | 6 1/2J   | 300                     |
| 16  | LT225/75R16 | 115/112Q | 10PR       | 223           | 744              | 6J       | 550                     |
|     | P235/65R16  | 107H     | XL         | 240           | 712              | 7J       | 340                     |
|     | P235/70R16  | 106H     | SL         | 240           | 736              | 7J       | 300                     |
|     | LT235/85R16 | 120/116Q | 10PR       | 235           | 806              | 6 1/2J   | 550                     |
|     | P245/70R16  | 107H     | SL         | 248           | 750              | 7J       | 300                     |
|     | P245/75R16  | 111H     | SL         | 248           | 774              | 7J       | 300                     |
|     | LT245/75R16 | 120/116Q | 10PR       | 248           | 774              | 7J       | 550                     |
|     | P255/70R16  | 111H     | SL         | 260           | 764              | 7 1/2J   | 300                     |
|     | P265/70R16  | 112H     | SL         | 272           | 778              | 8J       | 300                     |
|     | LT265/75R16 | 123/120Q | 10PR       | 267           | 804              | 7 1/2J   | 550                     |
| 17  | P215/60R17  | 96H      | SL         | 221           | 690              | 6 1/2J   | 300                     |
|     | P215/65R17  | 99H      | SL         | 221           | 712              | 6 1/2J   | 300                     |
|     | P225/60R17  | 99H      | SL         | 228           | 702              | 6 1/2J   | 300                     |
|     | P225/65R17  | 102H     | SL         | 228           | 724              | 6 1/2J   | 300                     |
|     | P235/60R17  | 102H     | SL         | 240           | 714              | 7J       | 300                     |
|     | P235/65R17  | 104H     | SL         | 240           | 738              | 7J       | 300                     |
|     | LT235/80R17 | 120/117T | 10PR       | 235           | 808              | 6 1/2J   | 550                     |
|     | P245/65R17  | 107H     | SL         | 248           | 750              | 7J       | 300                     |
|     | P245/70R17  | 110H     | SL         | 248           | 776              | 7J       | 300                     |
|     | LT245/70R17 | 119/116Q | 10PR       | 248           | 776              | 7J       | 550                     |
|     | LT245/75R17 | 121/118Q | 10PR       | 248           | 800              | 7J       | 550                     |
|     | P255/65R17  | 110H     | SL         | 260           | 764              | 7 1/2J   | 300                     |
|     | P255/70R17  | 112H     | SL         | 260           | 790              | 7 1/2J   | 300                     |
|     | P265/65R17  | 112H     | SL         | 272           | 776              | 8J       | 300                     |
|     | P265/70R17  | 115H     | SL         | 272           | 804              | 8J       | 300                     |
| 18  | LT265/70R17 | 118/115Q | 8PR        | 272           | 804              | 8J       | 450                     |
|     | P225/60R18  | 100H     | SL         | 228           | 727              | 6 1/2J   | 300                     |
|     | P235/60R18  | 103H     | SL         | 240           | 739              | 7J       | 300                     |
|     | P235/65R18  | 110H     | XL         | 240           | 763              | 7J       | 340                     |
|     | P245/60R18  | 105H     | SL         | 248           | 751              | 7J       | 300                     |
|     | P255/65R18  | 111T     | SL         | 260           | 789              | 7 1/2J   | 300                     |
|     | P265/60R18  | 110H     | SL         | 272           | 775              | 8J       | 300                     |
|     | P265/65R18  | 114T     | SL         | 272           | 801              | 8J       | 300                     |
|     | P265/70R18  | 116T     | SL         | 272           | 829              | 8J       | 300                     |
|     | P275/65R18  | 116T     | SL         | 279           | 815              | 8J       | 300                     |
| 19  | LT275/70R18 | 125/122Q | 10PR       | 279           | 843              | 8J       | 550                     |
|     | P255/60R19  | 113H     | XL         | 260           | 789              | 7 1/2J   | 340                     |
|     | P275/55R20  | 117V     | XL         | 284           | 810              | 8 1/2J   | 340                     |
| 20  | P275/60R20  | 119H     | XL         | 279           | 838              | 8J       | 340                     |

# HRT01



HANDLING



ANTI-WEAR



SAFE



WET GRIP



**SUV LANDRIDER**

## Excellent handling performance, better grip

The robust lower sidewall and bead design improves tire response and makes handling easy; Multi-angle grooves are designed to provide ample grip for the vehicle when accelerating and braking on straightaways and curves.

## Wear resistance, safe journey

Optimized placement of the tread blocks and grooves provides excellent ride comfort and wear resistance; All-season all-terrain tread rubber invention patent formula : rare earth catalytic polymer and high structural carbon black design, dramatically improve the tread rubber wear resistance.

## Passionate off-road driving experience

FEA-optimized tread block layout balances grounding stress distribution and improves street driving stability; Wide blocks with better off-road performance are used on the shoulders, enjoying the comfortable and safe driving in off-road conditions.



| Rim | Size          | LI/SS    | Load Range | Section Width | Overall Diameter | Std. Rim | Standard Pressure (Kpa) |
|-----|---------------|----------|------------|---------------|------------------|----------|-------------------------|
| 17  | LT265/70R17   | 118/115N | 8PR        | 272           | 804              | 8J       | 450                     |
|     | LT285/70R17   | 121/118N | 8PR        | 292           | 832              | 8 1/2J   | 450                     |
|     | LT315/70R17   | 121/118N | 10PR       | 323           | 874              | 9 1/2J   | 450                     |
|     | 33*12.50R17LT | 120Q     | 10PR       | 318           | 826              | 10J      | 450                     |
|     | 35*12.50R17LT | 119Q     | 10PR       | 318           | 877              | 10J      | 350                     |
| 18  | LT275/70R18   | 115/112Q | 6PR        | 279           | 843              | 8J       | 350                     |
|     | 33*12.50R18LT | 118Q     | 10PR       | 318           | 826              | 10J      | 450                     |
|     | 35*12.50R18LT | 123Q     | 10PR       | 318           | 877              | 10J      | 450                     |
|     | LT275/60R20   | 123/120N | 10PR       | 279           | 838              | 8J       | 550                     |
|     | LT275/65R20   | 126/123N | 10PR       | 279           | 866              | 8J       | 550                     |
| 20  | LT285/55R20   | 122/119N | 10PR       | 297           | 822              | 9J       | 550                     |
|     | LT305/55R20   | 121/118N | 10PR       | 316           | 844              | 9 1/2J   | 450                     |
|     | 33*12.50R20L  | 114Q     | 10PR       | 318           | 826              | 10J      | 450                     |
|     | 35*12.50R20LT | 121Q     | 10PR       | 318           | 877              | 10J      | 450                     |
|     | 37*13.50R20LT | 127Q     | 10PR       | 345           | 928              | 11J      | 450                     |
| 22  | 33*12.50R22LT | 109Q     | 10PR       | 318           | 826              | 10J      | 450                     |
|     | 35*12.50R22LT | 117Q     | 10PR       | 318           | 877              | 10J      | 450                     |
|     | 37*13.50R22LT | 123Q     | 10PR       | 345           | 928              | 11J      | 450                     |

# W01



HANDLING



ANTI-WEAR



SAFE



WET GRIP



AT WILDWOLF

## Extra long service life

The layered design in the block edge and the self-cleaning groove design can prevent stone and reduce damage to the tire.

## Super grip capability

Wider shoulder pattern design guarantees the stability and safety when sharp turning and braking.

## Anti-scratch, much safer

The shield simulation sidewall design can effectively reduce the damage probability by 80% when hitting the curb or other sharp objects.



| Rim | Size          | LI/SS    | Load Range | Section Width | Overall Diameter | Std. Rim | Standard Pressure (Kpa) |
|-----|---------------|----------|------------|---------------|------------------|----------|-------------------------|
| 15  | P235/75R15    | 105Q     | SL         | 235           | 733              | 6 1/2J   | 300                     |
|     | 31*10.5R15LT  | 109N     | 6PR        | 268           | 775              | 8 1/2J   | 350                     |
|     | P235/70R16    | 106Q     | SL         | 240           | 736              | 7J       | 300                     |
|     | LT235/85R16   | 106Q     | 10PR       | 235           | 806              | 6 1/2J   | 550                     |
|     | P245/75R16    | 111Q     | SL         | 248           | 774              | 7J       | 300                     |
| 16  | LT245/75R16   | 120/116N | 10PR       | 248           | 774              | 7J       | 550                     |
|     | P265/70R16    | 112Q     | SL         | 272           | 778              | 8J       | 300                     |
|     | P265/75R16    | 116Q     | SL         | 267           | 804              | 7 1/2J   | 300                     |
|     | LT265/75R16   | 119/116N | 8PR        | 267           | 804              | 7 1/2J   | 450                     |
|     | LT285/75R16   | 122/119N | 8PR        | 286           | 834              | 8J       | 450                     |
|     | 35*12.5R17LT  | 119Q     | 10PR       | 318           | 877              | 10J      | 350                     |
|     | LT235/80R17   | 120/117Q | 10PR       | 235           | 808              | 6 1/2J   | 550                     |
|     | P245/65R17    | 107Q     | SL         | 248           | 750              | 7J       | 300                     |
|     | LT245/75R17   | 121/118Q | 10PR       | 248           | 800              | 7J       | 550                     |
|     | P265/65R17    | 112Q     | SL         | 272           | 766              | 8J       | 300                     |
| 17  | P265/70R17    | 115Q     | SL         | 272           | 804              | 8J       | 300                     |
|     | LT265/70R17   | 118/115N | 8PR        | 272           | 804              | 8J       | 450                     |
|     | LT285/70R17   | 121/118N | 8PR        | 292           | 832              | 8 1/2J   | 450                     |
|     | P265/60R18    | 110Q     | SL         | 272           | 775              | 8J       | 300                     |
|     | P265/65R18    | 114Q     | SL         | 272           | 801              | 8J       | 300                     |
| 18  | LT265/70R18   | 124/121N | 10PR       | 272           | 829              | 8J       | 550                     |
|     | P275/65R18    | 116Q     | SL         | 279           | 815              | 8J       | 300                     |
|     | LT275/65R18   | 123/120N | 10PR       | 279           | 815              | 8J       | 550                     |
|     | LT275/70R18   | 115/112Q | 6PR        | 279           | 843              | 8J       | 350                     |
|     | 35*12.50R20LT | 121Q     | 10PR       | 318           | 877              | 10J      | 450                     |
| 20  | P275/55R20    | 117V     | XL         | 284           | 810              | 8 1/2J   | 340                     |
|     | P275/60R20    | 119Q     | XL         | 279           | 838              | 8J       | 340                     |
|     | LT275/65R20   | 126/123Q | 10PR       | 279           | 866              | 8J       | 550                     |
| 22  | P285/45R22    | 114Q     | XL         | 285           | 815              | 9 1/2J   | 340                     |

# T01



HANDLING



ANTI-WEAR



SAFE



WET GRIP



**MT WILDTIGER**

### Anti-scratch, much safer

Shield sidewall design with 6-7mm thicker than the ordinary tire, the tire damage probability is reduced by 80%.

### Super grip capability

The bionic tiger claw pattern provides strong grip on the mountain filed, desert, mud and other off-road conditions.

### Extra long service life

The bump design in the shoulder groove can prevent stone and reduce the damage to the tire.



| Rim | Size          | LI/SS    | Load Range | Section Width | Overall Diameter | Std. Rim | Standard Pressure (Kpa) |
|-----|---------------|----------|------------|---------------|------------------|----------|-------------------------|
| 15  | 31*10.50R15LT | 109N     | 6PR        | 268           | 775              | 8 1/2J   | 350                     |
|     | 33*12.50R15LT | 108N     | 6PR        | 318           | 826              | 10J      | 250                     |
|     | 35*12.50R15LT | 113Q     | 6PR        | 318           | 877              | 10J      | 250                     |
| 16  | 265/75R16LT   | 119/116N | 8PR        | 267           | 804              | 7 1/2J   | 450                     |
|     | 285/75R16LT   | 122/119N | 8PR        | 286           | 834              | 8J       | 450                     |
|     | 265/70R17LT   | 118/115N | 8PR        | 272           | 804              | 8J       | 450                     |
| 17  | 285/70R17LT   | 121/118N | 8PR        | 292           | 832              | 8 1/2J   | 450                     |
|     | 33*12.50R17LT | 120Q     | 10PR       | 318           | 826              | 10J      | 450                     |
|     | 35*12.50R17LT | 119Q     | 10PR       | 318           | 877              | 10J      | 350                     |
| 18  | 37*12.50R17LT | 124N     | 8PR        | 318           | 928              | 10J      | 350                     |
|     | LT275/70R18   | 115/112Q | 6PR        | 279           | 843              | 8J       | 350                     |
|     | LT285/65R18   | 121/118N | 8PR        | 292           | 827              | 8 1/2J   | 450                     |
| 20  | 33*12.50R18LT | 118Q     | 10PR       | 318           | 826              | 10J      | 450                     |
|     | 35*12.50R18LT | 123Q     | 10PR       | 318           | 877              | 10J      | 450                     |
|     | 33*12.50R20LT | 114Q     | 10PR       | 318           | 826              | 10J      | 450                     |
| 22  | 35*12.50R20LT | 121N     | 10PR       | 318           | 877              | 10J      | 450                     |
|     | 37*12.50R20LT | 126Q     | 10PR       | 318           | 928              | 10J      | 450                     |
|     | 33*12.50R22LT | 109Q     | 10PR       | 318           | 826              | 10J      | 450                     |
| 22  | 35*12.50R22LT | 117Q     | 10PR       | 318           | 877              | 10J      | 450                     |
|     | 37*13.50R22LT | 123Q     | 10PR       | 345           | 928              | 11J      | 450                     |